



## Protective Edging

Flexible, functional, versatile, design: the Special Profiles corner protectors are ideal for modern and minimalist furnishings, technical or professional environments.

Easy to install and maintain, sturdy for an excellent long-lasting result.

SPECIAL CORNER PVC	Spessore Thickness T	Dimensioni Size W	Lunghezza Length	Cod. Art./Item Code	PVC bianco White PVC		PVC marrone Brown PVC		Quantità per conf. Packing Quantity
	mm	mm	m		€/m	€/pz	€/m	€/pz	pz/pcs
PVC PVC	1	22	2,6	SPCO2222PVB26					110

- Material: Aisi 304 steel, aluminum, PVC

- Finish: Glossy or satin


- Bar length: see data sheets




SPECIAL CORNER PVC	1	28	3	SPCO2828PVB03					20
				SPCO2828PVM03					
PVC PVC									

- Quantity per pack: see data sheets

- Item Name: SpecialCORNER



SPECIAL CORNER AL	Spessore Thickness T	Dimensioni Size W	Lunghezza Length	Cod. Art./Item Code	Profili Anodizzati Argento Silver Anodized Profiles				Quantità per cont. Packing Quantity
					Serino Silver AAA	Bilante Bright Silver ABA	€/m	€/pz	
ALLUMINIO ALUMIUM	mm	mm	m		€/m	€/pz	€/m	€/pz	pz/pcs
	1	25	3	SPCO25251AAA27					10
				SPCO25251ABA27				16,02	




Available in various materials, finishes, sizes and shapes.

Can be used in recreational, private, professional, etc .. They are proposed for over or under installation.

SPECIAL CORNER AC	Spessore Thickness T	Dimensioni Size W	Dimensioni Size H	Lunghezza Length	Cod. Art./Item Code	Acciaio Lucido Polished Steel		Quantità per cont. Packing Quantity
						€/m	€/pz	
ACCIAIO STEEL	mm	mm	mm	m		€/m	€/pz	pz/pcs
	0,7	20		2,7	SPCO20207IL27			10
		30			SPCO30307IL27			



SpecialCornerPesa AC	Spessore Thickness T	Dimensioni Size W	Dimensioni Size H	Lunghezza Length	Cod. Art./Item Code	Acciaio Lucido Polished Steel		Quantità per cont. Packing Quantity
						€/m	€/pz	
ACCIAIO STEEL	mm	mm	mm	m		€/m	€/pz	pz/pcs
	0,7	30	8	2,7	SPCS30307ILO8			10
			10		SPCS30307IL10			



## **Main characteristics of the raw materials used by Special Profiles**

### **ALUMINUM**

Aluminum alloy (Al-Mg-Si) The profiles are made by extrusion or lamination and subsequent press bending. They have excellent resistance to the main chemical and atmospheric agents. Surface treatments through the company's proprietary systems, transform the material into:  
 Anodized aluminum: anodic oxidation with 8-10 microns of oxide thickness.  
 Polished Aluminum: anodic oxidation with 8-10 microns of oxide thickness.  
 Painted Aluminum: powder coated, with about 100 microns of paint thickness.  
 Not recommended for floor use.

### **STAINLESS STEEL - AISI 304**

The profiles are made by rolling and subsequent press bending. They have excellent resistance to the main chemical and atmospheric agents and excellent mechanical resistance. Surface treatments through the company's systems, transform the material into:

Polished and bright steel. Use both on the wall and on the floor, in hospitals, food, industry.

- Attention: the cutting edges are not stainless

**Rigid PVC** (Corner protectors)

Lead-free, impact-resistant, self-extinguishing rigid vinyl chloride. Good mechanical and abrasion resistance.

**Co-extruded PVC** - Rigid / Soft (expansion joints)

Co-extruded rigid vinyl chloride with soft PVC, leadfree, shockproof, self-extinguishing. Excellent mechanical resistance, to abrasion.

**PE-HD** (Tile spacers)

High density polyethylene, thermoplastic resin, excellent chemical stability and mechanical resistance. The high density (HD) increases its stiffness.

**POLYPROPYLENE** (External square and round corners)

Thermoplastic polymer, semi-crystalline, with good mechanical and abrasion resistance.

**Maintenance**

Avoid direct contact with concrete and its derivatives, if wet, descaling products and detergents that contain chlorine. Avoid using abrasive products that can scratch (abrasive sponges / metal wool). Immediately after laying proceed with a thorough cleaning of the surfaces with plenty of water / neutral / non-alkaline PH products, in particular remove cement, glue from the exposed surfaces.

**Measures and tolerances**

All information and drawings contained in this catalog are non-binding and subject to change without notice.

All dimensional data refer to nominal dimensions, subject to mechanical tolerances, according to the En- 22768 ISO-2768 -m standard.

**Special Profiles codes/Descriptions**

**Raw Material**

A= Aluminium  
F= Iron  
P= PVC  
I= Steel  
O= Brass

**Colours**

A=Silver      B=Light Brown  
O=Gold      M=Brown  
N=Black  
B=White  
G=Gray

**Surface treatments**

N=Natural      Z=Zincked  
A=Anodized      L=Bright  
V=Painted      O=Matt  
P=Brushed      S=SuperBright  
B=Brilliant



**Special Profiles** *a*



*brand of Mecc.Al Group*



- Via dei Laghi, 4 - Calcinelli 61036 Colli al Metauro (PU) – Italia Tel. +39.0721.8764.163

**Website :** [www.special-profiles.com](http://www.special-profiles.com) **e-mail:** [specialprofiles@meccal.com](mailto:specialprofiles@meccal.com)