

Profiles and innovative system for DIY, Tiles, Building systems



A complete series of profiles in Aluminum, Iron, Steel, Sheet metal completes the range of "Special Profiles" products: to carry out any work, construction or maintenance, for both the hobbyist and the professional.

Available in natural or satin or bright anodized or painted material.

All products are available in different lengths, from 1 meter to 3 meters.


All material is labeled with product code and description.

The iron profiles are protected with blistering, as are the sheets.

ANGOLARE ANGLE, EQUAL SIDE	Spessore Thickness T	Dimensioni Size WxH	completa il cod. art. (xxx) con il tipo di lunghezza complete item code (xxx) with the length	Lunghezza Length		Quantità per conf. Packing Quantity
				(1 m)	(2 m)	
				€/pz	€/pz	
mm	mm	Cod. Art./Item Code	€/pz	€/pz	pz/pcs	

ALLUMINIO ALUMINIUM

1,5	20x20	SPAN2020ANCxx			10
	25x25	SPAN2525ANCxx			
	30x30	SPAN3030ANCxx			
	40x40	SPAN4040ANCxx			




ELLE L PROFILE	1,5	40x20	SPEL4020ANCxx			10
		50x30	SPEL5030ANCxx			

ALLUMINIO ALUMINIUM



"U" U PROFILE	1,5	22,5x22,5	SPCU2222ANCxx			10
		25,5x25,5 <td>SPCU2525ANCxx</td> <td></td> <td></td>	SPCU2525ANCxx			

ALLUMINIO ALUMINIUM




lunghezze superiori a 2 m disponibili solo su richiesta - lunghezza massima fornibile m 2.7.
lengths longer than 2 m available on request only - maximum length available 2.7 m.

Completare il Cod. Art. con la lunghezza barra: ad es.barra da 1 metro -> SPP1007L01 (01 = 1m) (02 = 2m)
Complete item code with the bar's length: e.g. for 1 m -> SPP1007L01 (01 = 1m) (02 = 2m)

LAMIERE SHEET METAL	Spessore Thickness T	Dimensioni Size W	Dimensioni Size H			Quantità per conf. Packing Quantity
	mm	mm	mm	Cod. Art./Item Code	€/pz	pz/pcs


ALLUMINIO LISCIO
NATURALE
NATURAL ALUMINIUM
SHEETALUMINIUM



0,7	500	200	SPLA5020AN07		10
0,25			SPLA5020AN02		
0,7		400	SPLA5040AN07		
0,25			SPLA5040AN02		
0,7		500	SPLA5050AN07		
0,25			SPLA5050AN02		
0,7		600	SPLA5060AN07		
0,25			SPLA5060AN02		
0,7		1000	SPLA5010AN07		
0,25			SPLA5010AN02		

0,7	600	200	SPLA6020AN07		10
0,25			SPLA6020AN02		
0,7		400	SPLA6040AN07		
0,25			SPLA6040AN02		
0,7		500	SPLA6050AN07		
0,25			SPLA6050AN02		
0,7		600	SPLA6060AN07		
0,25			SPLA6060AN02		
0,7		1000	SPLA6010AN07		
0,25			SPLA6010AN02		


LAMIERE SHEET METAL	Spessore Thickness T	Dimensioni Size W	Dimensioni Size H			Quantità per conf. Packing Quantity
	mm	mm	mm	Cod. Art./Item Code	€/pz	pz/pcs
ALLUMINIO LISCIO ANODIZZATO SATINATO SILVER ANODIZED ALUMINIUM SHEET	0,7	500	200	SPLA5020AAA07		10
	0,25			SPLA5020AAA02		
	0,7		400	SPLA5040AAA07		
	0,25			SPLA5040AAA02		
	0,7		500	SPLA5050AAA07		
	0,25			SPLA5050AAA02		
	0,7		600	SPLA5060AAA07		
	0,25			SPLA5060AAA02		
	0,7		1000	SPLA5010AAA07		
	0,25			SPLA5010AAA02		



0,7	600	200	SPLA6020AAA07		10
0,25			SPLA6020AAA02		
0,7		400	SPLA6040AAA07		
0,25			SPLA6040AAA02		
0,7		500	SPLA6050AAA07		
0,25			SPLA6050AAA02		
0,7		600	SPLA6060AAA07		
0,25			SPLA6060AAA02		
0,7		1000	SPLA6010AAA07		
0,25			SPLA6010AAA02		

LAMIERE SHEET METAL		Spessore Thickness T	Dimensioni Size W	Dimensioni Size H			Quantità per conf. Packing Quantity
		mm	mm	mm	Cod. Art./Item Code	€/pz	pz/pcs


ALLUMINIO LISCIO
BRILLANTE
BRIGHT SILVER ANODIZED
ALUMINIUM SHEET








0,7	500	200	SPLA5020ABA07		10
0,25			SPLA5020ABA02		
0,7		400	SPLA5040ABA07		
0,25			SPLA5040ABA02		
0,7		500	SPLA5050ABA07		
0,25			SPLA5050ABA02		
0,7		600	SPLA5060ABA07		
0,25			SPLA5060ABA02		
0,7		1000	SPLA5010ABA07		
0,25			SPLA5010ABA02		

0,7	600	200	SPLA6020ABA07		10
0,25			SPLA6020ABA02		
0,7		400	SPLA6040ABA07		
0,25			SPLA6040ABA02		
0,7		500	SPLA6050ABA07		
0,25			SPLA6050ABA02		
0,7		600	SPLA6060ABA07		
0,25			SPLA6060ABA02		
0,7		1000	SPLA6010ABA07		
0,25			SPLA6010ABA02		

LAMIERE SHEET METAL						
ALLUMINIO CHICCO DI RISO NATURALE RICE GRAIN NATURAL ALUMINIUM SHEET	1,5	500	200	SPLC5020ANC02		10
			500	SPLC5050ANC02		
			600	SPLC5060ANC02		
	600	200	SPLC6020ANC02			
		600	SPLC6060ANC02			
		1000	SPLC6010ANC02			



LAMIERE SHEET METAL	Spessore Thickness T	Dimensioni Size W	Dimensioni Size H			Quantità per conf. Packing Quantity			
	mm	mm	mm	Cod. Art./Item Code	€/pz	pz/pcs			
ACCIAIO LISCIO BRILLANTE BRIGHT STEEL SHEET	0,7	500	200	SPLA5020IL07		10			
	0,25			SPLA5020IL02					
	0,7		400	SPLA5040IL07					
	0,25			SPLA5040IL02					
	0,7		500	SPLA5050IL07					
	0,25			SPLA5050IL02					
	0,7		600	SPLA5060IL07					
	0,25			SPLA5060IL02					
	0,7		1000	SPLA5010IL07					
	0,25			SPLA5010IL02					
	 		0,7	600	200		SPLA6020IL07		10
			0,25				SPLA6020IL02		
		0,7	400		SPLA6040IL07				
		0,25			SPLA6040IL02				
		0,7	500		SPLA6050IL07				
		0,25			SPLA6050IL02				
		0,7	600		SPLA6060IL07				
		0,25			SPLA6060IL02				
0,7		1000	SPLA6010IL07						
0,25			SPLA6010IL02						

LAMIERE STIRATE STRETCHED SHEETS	Spessore Thickness T	Dimensioni Size W	Dimensioni Size H		Ferro zincato Galvanized iron	Alluminio Naturale Natural aluminium	Acciaio Stainless steel	Quantità per conf. Packing Quantity
	mm	mm	mm	Cod. Art./Item Code	€/pz	€/pz	€/pz	pz/pcs
 	0,8	400	500	SPLS4050FZ08				10
				SPLS4050AN08				
			SPLS4050IL08					
			1000	SPLS4010FZ08				
				SPLS4010AN08				
			SPLS4010IL08					
		600	500	SPLS6050FZ08				
				SPLS6050AN08				
			SPLS6050IL08					
			1000	SPLS6010FZ08				
				SPLS6010AN08				
			SPLS6010IL08					
	AxB 6x10 Alluminio/Aluminium AxB 6x16 Acciaio/Steel							

Main characteristics of the raw materials used by Special Profiles

ALUMINUM

Aluminum alloy (Al-Mg-Si) The profiles are made by extrusion or lamination and subsequent press bending. They have excellent resistance to the main chemical and atmospheric agents. Surface treatments through the company's proprietary systems, transform the material into:

Anodized aluminum: anodic oxidation with 8-10 microns of oxide thickness.

Polished Aluminum: anodic oxidation with 8-10 microns of oxide thickness.

Painted Aluminum: powder coated, with about 100 microns of paint thickness. Not recommended for floor use.

STAINLESS STEEL - AISI 304

The profiles are made by rolling and subsequent press bending. They have excellent resistance to the main chemical and atmospheric agents and excellent mechanical resistance

Surface treatments through the company's systems, transform the material into:

Polished and bright steel. Use both on the wall and on the floor, in hospitals, food, industry.

- Attention: the cutting edges are not stainless

Rigid PVC (Corner protectors)

Lead-free, impact-resistant, self-extinguishing rigid vinyl chloride. Good mechanical and abrasion resistance.

Co-extruded PVC - Rigid / Soft (expansion joints)

Co-extruded rigid vinyl chloride with soft PVC, leadfree, shockproof, self-extinguishing. Excellent mechanical resistance, to abrasion.

PE-HD (Tile spacers)

High density polyethylene, thermoplastic resin, excellent chemical stability and mechanical resistance. The high density (HD) increases its stiffness.

POLYPROPYLENE (External square and round corners)

Thermoplastic polymer, semi-crystalline, with good mechanical and abrasion resistance.

Maintenance

Avoid direct contact with concrete and its derivatives, if wet, descaling products and detergents that contain chlorine. Avoid using abrasive products that can scratch (abrasive sponges / metal wool). Immediately after laying proceed with a thorough cleaning of the surfaces with plenty of water / neutral / non-alkaline PH products, in particular remove cement, glue from the exposed surfaces.

Measures and tolerances

All information and drawings contained in this catalog are non-binding and subject to change without notice.

All dimensional data refer to nominal dimensions, subject to mechanical tolerances, according to the En- 22768 ISO-2768 -m standard.

Special Profiles codes/Descriptions

Raw Material

A= Aluminium
Z=Zincked

F= Iron
P= PVC

Colours

A=Silver B=Light Brown

O=Gold M=Brown
N=Black

Surface treatments

N=Natural

A=Anodized L=Bright
V=Painted O=Matt

I= Steel
O= Brass

B=White
G=Gray

P=Brushed
B=Brilliant

S=SuperBright



Special Profiles a brand of Mecc.AI Group

- Via dei Laghi, 4 - Calcinelli 61036 Colli al Metauro (PU) - Italia Tel. +39.0721.8764.163

Website : www.special-profiles.com **e-mail:**
specialprofiles@meccal.com