







Profili per gradini
Stair nosing profiles

Stair nosing Profile

Dimensioni Size WxH	Lunghezza Length	Cod. Art./Item Code	Profili Anodizzati Argento Silver Anodized Profiles				Quantità per cont. Packing Quantity
			Satinato Silver AAA		Brillante Bright Silver ABA		
SPECIALSTEP-AL	mm	m	€/m	€/pz	€/m	€/pz	pz/pcs
ALLUMINIO ALUMINIUM  	2,7	SPST2520AAA27	3,92	10,58			10
		SPST2520ABA27			6,03	16,28	
		SPST4226AAA27	5,41	14,61			
		SPST4226ABA27			8,02	21,65	
SPECIALSTEPSC-AL ALLUMINIO ALUMINIUM  	2,7	SPS50010AAA27					10
		SPS50010ABA27					
		SPS50012AAA27					
		SPS50012ABA27					
SPECIALSTEPGROUND-AL ALLUMINIO ALUMINIUM  	2,7	SPSR0010AAA27					10
		SPSR0010ABA27					
		SPSR0012AAA27					
		SPSR0012ABA27					

- • Functional, versatile, design: the aluminum stair nosing of Special Profiles are ideal for modern furnishings, technical environments, professional offices, public places.
- • They cover any cracks in the upholstery and create a useful anti-slip.
- • Easy to install and maintain, sturdy for an excellent long-lasting result.
- • Top-laying and under-laying models, with round or square section, with various sizes available.
-
- • Satin or bright anodized finishes, to adapt to any environment.
- • Material: Aluminum
- • Finish: Satin or Brilliant
- • Height: various sizes / shapes available, as per technical drawing.
- • Bar length: 2.7 m
- • Quantity per pack: 10 bars
- • Item Name: SPECIALSTEP-AL SPECIALSTEPSQ-AL SPECIALSTEPROUND-AL
- • AAA: Silver Anodized Aluminum
- • ABA: Bright Anodized Aluminum

Main characteristics of the raw materials used by Special Profiles

ALUMINUM

Aluminum alloy (Al-Mg-Si) The profiles are made by extrusion or lamination and subsequent press bending. They have excellent resistance to the main chemical and atmospheric agents. Surface treatments through the company's proprietary systems, transform the material into:
 Anodized aluminum: anodic oxidation with 8-10 microns of oxide thickness.
 Polished Aluminum: anodic oxidation with 8-10 microns of oxide thickness.
 Painted Aluminum: powder coated, with about 100 microns of paint thickness.
 Not recommended for floor use.

STAINLESS STEEL - AISI 304

The profiles are made by rolling and subsequent press bending. They have excellent resistance to the main chemical and atmospheric agents and excellent mechanical resistance. Surface treatments through the company's systems, transform the material into:
 Polished and bright steel. Use both on the wall and on the floor, in hospitals, food, industry.
 • Attention: the cutting edges are not stainless

Rigid PVC (Corner protectors)

Lead-free, impact-resistant, self-extinguishing rigid vinyl chloride. Good mechanical and abrasion resistance.

Co-extruded PVC - Rigid / Soft (expansion joints)

Co-extruded rigid vinyl chloride with soft PVC, leadfree, shockproof, self-extinguishing. Excellent mechanical resistance, to abrasion.

PE-HD (Tile spacers)

High density polyethylene, thermoplastic resin, excellent chemical stability and mechanical resistance. The high density (HD) increases its stiffness.

POLYPROPYLENE (External square and round corners)

Thermoplastic polymer, semi-crystalline, with good mechanical and abrasion resistance.

Maintenance

Avoid direct contact with concrete and its derivatives, if wet, descaling products and detergents that contain chlorine. Avoid using abrasive products that can scratch (abrasive sponges / metal wool). Immediately after laying proceed with a thorough cleaning of the surfaces with plenty of water / neutral / non-alkaline PH products, in particular remove cement, glue from the exposed surfaces.

Measures and tolerances

All information and drawings contained in this catalog are non-binding and subject to change without notice.
 All dimensional data refer to nominal dimensions, subject to mechanical tolerances, according to the En- 22768 ISO-2768 -m standard.

Special Profiles codes/Descriptions

Raw Material

A= Aluminium
 F= Iron
 P= PVC
 I= Steel
 O= Brass

Colours

A=Silver B=Light Brown
 O=Gold M=Brown
 N=Black
 B=White
 G=Gray

Surface treatments

N=Natural Z=Zincked
 A=Anodized L=Bright
 V=Painted O=Matt
 P=Brushed S=SuperBright
 B=Brilliant



Special Profiles spa



brand of Mecc.Al Group



- Via dei Laghi, 4 - Calcinelli 61036 Colli al Metauro (PU) – Italia Tel. +39.0721.8764.163

Website : www.special-profiles.com **e-mail:** specialprofiles@meccal.com